



Information required by EN 16139:2013

European Standards used:

EN 16139:2013 - Furniture - Strength, durability and safety - Requirements for non-domestic seating

EN 1728/AC:2012 - Domestic furniture - Seating - Test methods - Determination of strength and durability

EN 1022:2005 - Domestic furniture - Seating - Determination of stability

EN 1335:2009 - Office furniture - Office work chair - Part 3: Test methods

Details of tested seating:

Model:	Maki			Type:	Chair		
Length:	1120 mm	Depth:	950 mm	Height:	720 mm	Weight:	27.54 kg
Materials:	Upholstery - metal						

Details of defects observed before testing:

None.

Details of any deviations from this standard:

None.

Any variation from the specified temperature range:

None.

Test result:

See appendix A.

Name and address of the test facility:

Danish Technological Institute, Gregersensvej, Taastrup 2630, Denmark

Date of test:

2020-06-10 to 2020-06-22

Photo of the received sample:



MAKI
Easy Chair
By Jin Kuramoto



OFFECCT

PRODUCT INFORMATION

A solitary and social icon based on minimalism and diversity. A strong and iconic shape that stands out in every room and at the same time a flexible and social team player designed to be combined in different formations. Maki easy chair has a simple, innovative and self-evident form offering plenty of possibilities.

"The chair has a strong and symbolic shape, while being flexible in applications and functions. It can be used to work, rest, meet and wait – as a lone icon with a strong personal presence or together in different formations", says Jin Kuramoto.

TECHNICAL INFORMATION

Available for the United States market.

Metal frame with molded cold foam. Fully upholstered in fabric. Stand: Legs in black matt structure lacquered RAL 9005 alt. gray Ral 7046 with ABS glides.




FABRIC



RAL 9005

OFFECCT

MAKI



H 715, S 425, W 1090, D 955/540

H 28,15", SH 16,73", W 42,91", D 37,6"/ 21,26"

Test Report

Report Number:
928152-1



**DANISH
TECHNOLOGICAL
INSTITUTE**

Gregersensvej 1
DK-2630 Taastrup
+45 72 20 20 00
info@teknologisk.dk
www.teknologisk.dk

Page 1 of 3
Init.: JJU/JHA
Order no.: 928152
Encl.: 2

Assignor: Offecct AB, Box 100, SE-543 21, Tibro, Sweden

Item : Maki

Sampling: The assignor confirms having selected the product. The product was forwarded by the assignor and received at Danish Technological Institute on 8 June 2020.

Period: The test took place from 10 June 2020 to 22 June 2020.

Method: EN 16139:2013, Furniture - Strength, durability and safety - Requirements for non domestic seating
EN 16139 Test severity L1: General use: E.g. in office buildings, showrooms, public halls, function rooms, cafés, restaurants, canteens, banks, bars.
Additional information is given in enclosure B.

Test results: **Passed.**
The results are shown in enclosure A.

Terms: This test was conducted accredited in accordance with international requirements (ISO/IEC 17025:2005) and in accordance with the General Terms and Conditions of Danish Technological Institute. The test results solely apply to the tested item. This test report may be quoted in extract only if Danish Technological Institute has granted its written consent.

Place: Danish Technological Institute, Taastrup, Building and Construction

Signature: This document is only valid with a digital signature from Danish Technological Institute.
Date of issue 24 June 2020.
Jesper Junge Pedersen
Consultant



DIGITALLY SIGNED DOCUMENT

25 June 2020

DANISH TECHNOLOGICAL INSTITUTE



DANAK

TEST Reg.no. 2



Test of Model: Maki

Loading according to test severity L1.

Test no.	Test	Test Method	Cycles	Load	Result
4.1	General	EN 16139, 4.1			Passed
4.2.2	Shear and squeeze points under influence of powered mechanisms	EN 16139, 4.2.2			N/A
4.2.3	Shear and squeeze points during use	EN 16139, 4.2.3			Passed
4.3.2	Swivelling chairs	EN 1335			N/A
4.3.3	Non swivelling chairs	EN 1022			Passed
4.4	Rolling resistance of the unloaded chair	EN 16139, 4.4			N/A
5	Strength and durability requirements	EN 16139, 5			Passed
6.1.1	Seat static load and back static load test	EN 1728, 6.4	10 10	Seat: 1600 N Back: 560 N	Passed
6.1.2	Seat front edge static load	EN 1728, 6.5	10	Seat: 1300 N	Passed
6.1.3	Vertical load on back rests	EN 1728, 6.6	10	Seat: 1300 N Back: 600 N	Passed
6.1.4	Foot rest static load test	EN 1728, 6.8	10		N/A
6.1.4	Leg rest static load test	EN 1728, 6.9	10		N/A
6.1.5	Arm rest sideways static load test	EN 1728, 6.10	10		N/A
6.1.6	Arm rest downwards static load test	EN 1728, 6.11	5		N/A
6.1.7	Vertical upwards static load on arm rests	EN 1728, 6.13	10		N/A
6.1.8	Combined seat and back durability test	EN 1728, 6.17	100000 100000	Seat: 1000 N Back: 300 N	Passed
6.1.9	Seat front edge durability test	EN 1728, 6.18	50000	800 N	Passed
6.1.10	Arm rest durability test	EN 1728, 6.20	30000		N/A
6.1.11	Foot rest durability test	EN 1728, 6.21	50000		N/A
6.1.12	Leg forward static load test	EN 1728, 6.15	10	Edge: 450 N (Seat: 1000 N)	Passed
6.1.13	Legs sideways static load test	EN 1728, 6.16	10	Edge: 400 N (Seat: 1000 N)	Passed
6.1.14	Seat impact test	EN 1728, 6.24	10	240 mm	Passed
6.1.15	Back impact test	EN 1728, 6.25	10	210 mm / 38 °	Passed
6.1.16	Arm Impact Test	EN 1728, 6.26	10		N/A
6.1.17	Drop test (multiple seating)	EN 1728, 6.27.1	2 x 5		N/A
6.1.18	Auxiliary writing surface static load test	EN 1728, 6.14			N/A
6.1.19	Auxiliary writing surface durability test	EN 1728, 6.22	10000		N/A
7	Information for use	EN 16139, 7			N/A